

# LM22-L200

## 21.5" FHD LCD Monitor



#### Features:

- $\cdot$  Industrial level LCD panel, suitable for continuous 24/7 operation
- $\cdot$  5ms response time for no motion blur, judder or ghosting
- · High fidelity digital processing for a brilliant and vivid video
- · Included desk stand is easily removable for standard VESA mounting
- · Support HDCVI/HDTVI/AHD/CVBS signal input and output
- · Built in speakers













#### **Technical Specification**

#### Model

Model	LM22-L200
Display	
Screen Size	21.5"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	200cd/ m²
Contrast	1000:1
Display color	16.7M(8bit)
Viewing Angle(H/V)	H170°(H)/V160°(V)
Viewing Angle(H/V)  Response Time	H170°(H)/V160°(V) 5ms

#### Signals

Input	HD×1 (support HDCVI, HDTV HDMI×1, BNC×1, Audio×1	'I, AHD, CVBS), VGA×1,
Output	HD×1 (support HDCVI, HDTVI, AHD, CVBS)	
	Speaker	2W×2

#### General

Power Supply AC100~240V (+/-10%), 50/60 Hz
--

Consumption (Standard)	≤30W	
Consumption (Standby)	≤0.5W	
Туре	Internal	
Net Weight	3.8 kg (8.4lb)	
Gross Weight	5.0kg (11.0lb)	
Bezel Width	24mm (U), 19.4mm (R/L), 25.4mm (B)	
Wall Mount	100×100mm (3.9"×3.9")	
Dimension without standard (W×H×D)	516.60x316.70x51.20mm (20.3"×12.5"×2.0")	
Package(W×H×D)	565x420x116mm (22.2"×16.5"×4.6")	
Work Environment	Temperature	0°C~ 40°C
	Humidity	10%~85%

#### Accessory

Standard	VGA cable, power cable, pedestal
Optional	Hanging bracket
Certifications	
Certifications	CE/FCC

# Essential Security Series | LM22-L200

### **Dimensions**(mm)



