

LM43-S400

43" UHD LED Monitor



Features:

- 4K Ultra-HD resolution
- Industrial level LCD panel, suitable for continuous 24/7 operation
- Slim 8mm narrow bezel design
- Built-in 3D COMB filter and 3D Noise Reduction
- 8ms response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° wide uninterrupted viewing angle
- Using tamper-proof metal housing
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Wide array of connectivity options HDMI, DP, VGA, USB, Audio, RS232



Technical Specification

Model

Model	LM43-S400
-------	-----------

Display

Screen Size	43"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	450cd/m ²
Contrast	4000:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	8(GTG) ms
Refresh Rate	60Hz

Signals

Input	DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1	
Output	RJ45(RS232)×1	
	Speaker	5W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	<105W	
Consumption (Standby)	≤0.5W	
Type	Internal	
Net Weight	16.6kg (36.6lb)	
Gross Weight	27kg (59.5lb)	
Bezel Width	8mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimension without standard (W×H×D)	960.7×550.7×65.0mm (37.8"×21.7"×2.6")	
Package(W×H×D)	1145×730×255mm (45.1"×28.7"×10.0")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%~85%

Accessory

Standard	HDMI cable, power cable, hanging bracket
Optional	Pedestal

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

