

DHI-VTH5422HW-W/DHI-VTH5422HB-W

2-wire IP & Wi-Fi Indoor Monitor



- 7" TFT capacitive touchscreen, 1024 × 600
- · 6-channel alarm input and 1-channel alarm output
- Wi-Fi
- · Door station and IPC monitor
- H.265 and H.264 video decoding
- · 2-wire digital communication



| Technical | Specification | |
|-----------|---------------|--|
| | opcontoation | |

| System | | |
|---------------------|---|--|
| Main Processor | Embedded processor | |
| Operating System | Embedded Linux operating system | |
| Interoperability | ONVIF; SDK | |
| Network Protocol | RTSP; RTP; SIP; DNS; SSH | |
| Basic | | |
| Screen Type | Capacitive touchscreen | |
| Display | 7" TFT | |
| Screen Resolution | 1024 × 600 | |
| Audio Compression | G.711a; G.711u; PCM | |
| Audio Input | 1 | |
| Audio Output | Built-in speaker | |
| Audio Mode | 2-way Audio | |
| Audio Enhancement | Echo suppression | |
| Audio Bit Rate | 16 kHz; 16 Bit | |
| Function | | |
| Communication Mode | Digital 2-wire | |
| Information Release | Receive and view text information released by the management center | |
| Leave Videos | Yes (insert an SD card into the indoor monitor) | |
| DND Mode | Do not disturb period can be set; Do not disturb mode | |
| | | |

| Number of Extensions | Villa: 3 Apartment: 2 Wi-Fi intercom: 1 main monitor, 2 extension monitors |
|------------------------------|---|
| Wi-Fi | Yes |
| Wireless Standard | IEEE802.11b/802.11g/802.11n |
| Wireless Frequency Range | 2,412–2,472 MHz |
| Wireless Security Encryption | WPA/WPA2; WPA-PSK/WPA2-PSK |
| Storage | Micro SD card (up to 64 GB) |
| Performance | |
| Casing | PC + ABS |
| Port | |
| RS-485 | 1 |
| Alarm Input | 6 |
| Alarm Output | 1 |
| Power Output | 1 (12 V/200 mA) |
| Door Bell | Yes (use any alarm input port) |
| Network | One two-wire port and one 10 Mbps/100 Mbps Ethernet port (one of them can be selected) |
| General | |
| Appearance Color | White/Black |
| Power Supply | 48 VDC 1.25 A |
| Installation | Surface mount |
| Certifications | CE; FCC |
| Dimensions | 189.0 mm × 130.0 mm × 26.9 mm (7.44" × 5.12" × 1.06") |

VTH5 Series | DHI-VTH5422HW-W/DHI-VTH5422HB-W

| Operating Temperature | -10 °C to +55 °C (+14 °F to 131 °F) |
|-----------------------|--|
| Operating Humidity | 10%-95% RH (non-condensing) |
| Operating Altitude | Beneath 3000 m (9842.52 ft) |
| Power Consumption | Standby \leq 2 W; working \leq 6 W |
| Net Weight | 0.35 kg (0.78 lb) |
| Gross Weight | 0.56 kg (1.23 lb) |

Ordering Information

| Туре | Model | Description |
|-------------------|-------------------------------------|----------------------------------|
| IP Indoor Monitor | DHI-VTH5422HW-W/ DHI-VTH5422HB-W | 2-wire IP & Wi-Fi Indoor Monitor |

Installation



Dimensions (mm[inch])









Application



Rev 002.000 © 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.