MIXING AMPLIFIERS MA Mixing Amplifiers



Compact size mixing amplifiers for music and speech.

MA 30X

30W power, low and high impedance outputs, AUX/Phono and microphone inputs, tone control. Priority input, activated by closing contacts on rear panel. Perfect for use in small size applications such as shops, bars or restaurants, and there's no need for professional installation assistance.



Technical Specifications	MA 30X
Output power	30 W
AC power consumption	57 VA
Power supply	~230 V/ 50Hz
Outputs	Low impedance output – 4 $\Omega$ , 8 $\Omega$ , 16 $\Omega$ (Screw terminal connectors) Hi impedance outputs – 100 V (Screw terminal connectors)
Inputs	Microphones: sensitivity - 55 dB, impedance 10 k $\Omega$ , connectors - unbalanced 6.3 mm TRS Jack AUX: sensitivity - 20 dB, impedance 10 k $\Omega$ , connectors - Stereo RCA PHONO: sensitivity - 55 dB, impedance 10 k $\Omega$ , connectors - Stereo RCA
Frequency response	50 Hz - 20 kHz
THD	Less than 1 % at 1 kHz rated power
Signal / noise ratio	>55 dB
Tone control	Bass $\pm 12$ dB, Middle $\pm 12$ dB, Treble $\pm 12$ dB
Controls	Input level control, tone control, master
Indicators	Power
Dimensions	320 mm $\times$ 190 mm $\times$ 75 mm
Weight	5 kg
Colour	Black (RAL 9017)