



1622

IKALL SIMPLEBUS AUDIO SPEAKER



SB TOP

Audio speaker unit for Simplebus system, complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming user calls. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus a 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all SBTOP functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.



1622

IKALL SIMPLEBUS AUDIO SPEAKER

MAIN FEATURES

Audio system:	Yes
Audio system:	Yes
Audio/video system:	Yes
Clamps:	L L V+V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55

FUNCTIONS

Key button function:	Yes
----------------------	-----

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes

GENERAL DATA

Product height (mm):	55
Product width (mm):	102
Product depth (mm):	38

COMPATIBILITY

Simplebus 1 audio system:	Yes
---------------------------	-----

ELECTRICAL SPECIFICATIONS

Door release (dry contact bridge):	Yes
Door release (direct current output):	Yes