



1682

IKALL VIP AUDIO ONLY SPEAKER



Audio-video unit for VIP system including terminal block complete with front-adjustable mini lens colour camera, LED camera lighting. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: art.33400, 33401, 33402. Dimensions: 102x55x38 mm.


1682

IKALL VIP AUDIO ONLY SPEAKER

MAIN FEATURES

| | |
|-----------------------------|---|
| Audio system: | Yes |
| Audio/video system: | Yes |
| Power supply voltage: | 30 ÷ 57 |
| Clamps: | TX- TX+RX- RX+V- V+RTE GND SE COM NC NO |
| Microphone: | Yes |
| Microphone volume control: | Yes |
| Loudspeaker: | Yes |
| Loudspeaker volume control: | Yes |
| Operating temperature (°C): | -25 ÷ 55 |

SOFTWARE/FIRMWARE SPECIFICATIONS

| | |
|----------------|--|
| IP assignment: | |
|----------------|--|

FUNCTIONS

| | |
|----------------------|-----|
| Key button function: | Yes |
|----------------------|-----|

HARDWARE SPECIFICATIONS

| | |
|----------------------|-----|
| Visual signalling: | Yes |
| Acoustic signalling: | Yes |
| Speech synthesis: | Yes |

GENERAL DATA

| | |
|----------------------|-----|
| Product height (mm): | 55 |
| Product width (mm): | 102 |
| Product depth (mm): | 38 |

COMPATIBILITY

| | |
|-------------|-----|
| Vip system: | Yes |
|-------------|-----|

CONNECTIVITY

| | |
|-----------------|---|
| Ethernet ports: | 1 |
|-----------------|---|

ELECTRICAL SPECIFICATIONS

| | |
|---------------------------------------|-----|
| Door release (dry contact bridge): | Yes |
| Door release (direct current output): | Yes |