



2738W/A

SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET



Mini series door-entry phone with handset for Simplebus 2 audio systems. Equipped with a key button, button for additional services such as calls to the porter switchboard..., call volume adjustment, Silent mode (Privacy) and floor call input. Correct positioning of the handset on the base is facilitated by invisible magnetised panels. The additional board art. 2735 is available to purchase separately, for an additional button with voltage free contacts and call repetition. Fitted with terminal art. 1214/2C.

AWARDS

DESIGN
MILANO



2738W/A

SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET

GENERAL DATA

Height (mm)	190
Depth (mm)	28
Type of finishing materials	ABS
Product weight (g)	300
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes

AUDIO FEATURES

Microphone	9.6 (ø) x 6.9mm, omnidirectional
Loudspeaker	50mm (Ø), 50 Ohm, 0.25W
Technologies implemented	Full-Duplex

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷35VDC
Maximum absorption (W)	0.8

HARDWARE FEATURES

Type of buttons	Mechanical
Service buttons	Lock-release
Clamps	L L CFP CFP



2738W/A

SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET

HARDWARE FEATURES

Number of inputs (n°)	1
-----------------------	---

SETTINGS

Ringtone volume	Yes
-----------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°C)	-5 ÷ 40
----------------------------	---------

Operating humidity (RH max) (%)	25 ÷ 90
---------------------------------	---------

Environmental class	III
---------------------	-----

CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
-------------------	--

GENERAL FEATURES

Door opener	Yes
-------------	-----

Absorption during call (mA)	25
-----------------------------	----

Absorption during communication (mA)	20
--------------------------------------	----

Maximum current absorption (mA)	25
---------------------------------	----

Minimum current absorption (mA)	1
---------------------------------	---

CPS call	Yes
----------	-----

Actuator control	Yes
------------------	-----

Outside door call input	Yes
-------------------------	-----

Silent mode (Privacy)	Yes
-----------------------	-----