« Comelif





#### 6601W





Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire SimplebusTop Colour systems. Dimensions 142.5x147x23 mm.





#### 6601W

## ICONA MONITOR, SBTOP

MAIN FEATURES	
Audio system:	No
Audio/video system:	Yes
Flush-mounted:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Induction loop function:	No
Type of display:	LCD
Display size (inch):	4,3'' 16:9
Touch screen display:	No
Display resolution HxV (mm):	480x272
B/W or colour display:	Color
Product colour:	White RAL9003
Sensitive Touch technology:	Yes
Total buttons:	9
Comaptibility with Video Entry Comelit App:	No

FUNCTIONS
Actuator control function:

Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Priority calls:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Call to group addresses:	Yes
Call forwarding:	Yes
Privacy function:	Yes
Doctor:	Yes
Redial:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	Yes
Privacy conversation function:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS	
Removable terminals:	Yes



#### 6601W

# ICONA MONITOR, SBTOP

HARDWARE SPECIFICATIONS	
Type of finish:	Plastic

SETTINGS	
Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes
Display brightness control:	Yes
Display contrast control:	Yes

GENERAL DATA	
Product height (mm):	147
Product width (mm):	142,5
Product depth (mm):	23

COMPATIBILITY	
Simplebus Top audio/video system:	Yes
Building Kit audio/video system:	Yes
Kit audio/video system:	Yes

TECHNICAL CHARACTERISTICS	
Power supply voltage:	22 ÷ 28
Maximum current absorption (mA):	400
IP protection rating:	IP30
Operating temperature (°C):	-5 ÷ 40
RH max operating humidity (%):	25 ÷ 75
Product weight (g):	698,53
Clamps:	L L -+CFP1 CFP2 S+S- IN1 IN2



### 6601W

ICONA MONITOR, SBTOP

	,	
ACCESSORIES		
	6117	PLANUX, SMART, ICONA FLUSH BACKBOX Flush mounted box for Planux,Smart and Icona monitors Dimensions: 132x132x50mm
	6118	PLANUX CLIPS FOR DRY LINED WALLS Installation kit for plasterboard walls.
	6617	Flush-mounted box for plasterboard. Icona Flush-mount box allowing mounting of Icona series monitors on plasterboard and/or cement walls. Dimensions: 129x129x50 mm
	6620	WALL BRACKET FOR ICONA MONITOR Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.
	6612A	DESK BASE FOR ICONA MONITOR Desk base installation accessory for Icona monitor.