



**84611**

## QUADRA AND ICONA SINGLE-FAMILY KIT, SIMPLEBUS SYSTEM



SB2

2-wire Simplebus door entry monitor kit comprised of: 1 Quadra series wall-mounted external unit art. 4893M, 1 power supply unit art. 1209, 1 Mini series color monitor with handset art. 6601W, 1 flush-mounted box art. 6117, 1 wall-mounted bracket art. 6620, 1 distribution terminal art. 1214/2C and 1 line closure terminal art. 1216.

## AWARDS

DESIGN  
MILANO



DESIGN PLUS  
powered by building



**84611**

## QUADRA AND ICONA SINGLE-FAMILY KIT, SIMPLEBUS SYSTEM

KIT PRODUCT



**6601W**

ICONA MONITOR, S2

Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 Colour systems. Dimensions 142.5x147x23 mm.

### GENERAL DATA - 6601W

Product height (mm):	147
Product width (mm):	142,5
Product depth (mm):	23
Product weight (g):	500
Product color:	White RAL9003, base grey RAL7001
Material:	ABS, PMMA
Flush mounting:	Yes, with a dedicated accessory
Wall mounting:	Yes, with a dedicated accessory
Desk base-mounted:	Yes, with a dedicated accessory



**4893M**

QUADRA ENTRANCE PANEL W/ BUTTONS. 2 WIRES

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 95x195x28 mm.

### MAIN FEATURES - 4893M

Type:	Monoblock
Type of finish:	Die-cast aluminum
Audio/video system:	Yes
Wall-mounted:	Yes
Type of sensor:	1/4" CMOS
Lens size (mm):	2,1
Diagonal viewing angle (°):	100
Minimum colour lighting (lux):	0,1
Horizontal resolution (TVL):	550
Signal/noise ratio (dB):	48

The technical specifications are subject to variations without warning.



**84611**

## QUADRA AND ICONA SINGLE-FAMILY KIT, SIMPLEBUS SYSTEM

### MAIN FEATURES - 4893M

Maximum current absorption (mA):	250
Clamps:	LL RTE COM DO SE- SE+C NC NO
Buttons to call:	Yes
Total buttons:	4
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55
RH operating humidity (%):	25 ÷ 75
IP protection rating (IP code):	IP54
Vandal Resistant rating (IK code):	IK08
Backlighting colour:	White

**1216**

#### SIMPLEBUS/KIT SYSTEM TERMINAL



Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.

**6117**

#### PLANUX, SMART, ICONA FLUSH BACKBOX



Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm

### MAIN FEATURES - 6117

Height (mm):	132
Width (mm):	132
Depth (mm):	50

**6620**

#### WALL BRACKET FOR ICONA MONITOR



Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.



**84611**

## QUADRA AND ICONA SINGLE-FAMILY KIT, SIMPLEBUS SYSTEM

### MAIN FEATURES - 6620

Height (mm):	141,6
Width (mm):	136,6
Depth (mm):	13,8
Weight (g):	40



**1209**

#### 2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).

### MAIN FEATURES - 1209


Supply voltage (VAC):	110÷240
Input connector:	Terminal block
Applicable to DIN rail:	Yes
Number of DIN modules:	6
Max. current delivered (A):	1,2



**84611**

## QUADRA AND ICONA SINGLE-FAMILY KIT, SIMPLEBUS SYSTEM

### ACCESSORIES



**4791**

Adapter plate for Quadra

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm



**4792**

RAIN SHIELD FOR QUADRA ENTRANCE PANEL

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.



**4793MB**

BLACK FACEPLATE FOR QUADRA W/BUTTONS

Black faceplate for Quadra entrance panel with mechanical buttons



**4793MC**

CORTEN FACEPLATE FOR QUADRA W/BUTTONS

Corten color faceplate for Quadra entrance panel with mechanical buttons.



**4793MA**

ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS

Aluminium colour faceplate for Quadra entrance panel with mechanical buttons



**1217**

NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates



**84611**

## QUADRA AND ICONA SINGLE-FAMILY KIT, SIMPLEBUS SYSTEM

### ACCESSORIES



**1235A**

#### NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



**6117**

#### PLANUX, SMART, ICONA FLUSH BACKBOX

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm



**6118**

#### PLANUX, SMART, ICONA CLIPS FOR DRY LINED WALLS

Installation kit for plasterboard walls for Planux, Smart and Icona monitors.



**6620**

#### WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.



**6612**

#### DESK BASE FOR ICONA MONITOR

Adjustable tilt desk base converts the Smart monitor into a desktop version. Complete with 1 x 2 m labelled RJ45 cable for connecting the monitor terminals to the clasp or to a residential series jack. Dimensions: 145x190x120 mm.



**1209**

#### 2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).



**84611**

## QUADRA AND ICONA SINGLE-FAMILY KIT, SIMPLEBUS SYSTEM

### ACCESSORIES



**1229A**

**ADDITIONAL RINGTONE ACCESSORY. S2**

Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24mm.



**1256**

**ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR**

Intelligent Simplebus device for controlling a 12-24 V relay contact. If used in mixed audio/video systems, the actuator relay needs a video filter to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 66X85X35 (4 DIN modules).



**1404**

**DIGITAL SWITCHING DEVICE. 2-WIRE SYSTEM**

Audio/video switching module for Simplebus 2 2-wire digital systems. To be used in systems with more than one entrance. Power supply from bus line. Dimensions: 60x85x35 mm (4 DIN modules).



**1405**

**DIGITAL EXCHANGE 2 QUADRA INPUTS. S2**

Audio/video switching module for audio/video kit systems. For use in systems with a maximum of 2 entrances with Quadra series external unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN modules).



**1409**

**ACCESSORY FOR REMOTE COLOUR CAMERAS, 2-WIRE SYSTEM**

Remote camera module for Simplebus 2 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).