



8461V





2-wire Simplebus door entry monitor kit comprised of: 1 Quadra series wall-mounted external unit art. 4893M, 1 power supply unit art. 1209, 1 Handsfree Mini series colour monitor art. 6721W, 1 distribution terminal art. 1214/2C and 1 line closure terminal art. 1216.

AWARDS













8461V

QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.

KIT PRODUCT



6721W

MINI HANDSFREE MONITOR, S2

Wall-mounted hands-free monitor with full-duplex audio and 4.3" / 16:9 colour screen. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies. Equipped as standard with 5 sensitive touch back-lit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard. Option of adding 3 additional buttons with accessory Art. 6734W. Complete with 2 x 8-position DIP-SWITCH for user code programming and button programming. The wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C are included. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 115x160x22mm.

GENERAL DATA - 6721W			
Product height (mm):	160		
Product width (mm):	115		
Product depth (mm):	22		
Product weight (g):	500		
Product color:	White RAL9003		
Material:	ABS		
Wall mounting:	Yes		
Desk base-mounted:	Yes, with a dedicated accessory		



4893M

QUADRA ENTRANCE PANEL W/ BUTTONS. 2 WIRES

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 95x195x28 mm.

MAIN FEATURES - 4893M			
Туре:	Monoblock		
Type of finish:	Die-cast aluminum		
Audio/video system:	Yes		
Wall-mounted:	Yes		
Type of sensor:	1/4" CMOS		
Lens size (mm):	2,1		
Diagonal viewing angle (°):	100		
Minimum colour lighting (lux):	0,1		
Horizontal resolution (TVL):	550		
Signal/noise ratio (dB):	48		
Maximum current absorption (mA):	250		
Clamps:	LL RTE COM DO SE- SE+C NC NO		

The technical specifications are subject to variations without warning.



8461V

QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.

MAIN FEATURES - 4893M			
Buttons to call:	Yes		
Total buttons:	4		
Microphone volume control:	Yes		
Loudspeaker volume control:	Yes		
Operating temperature (°C):	-25 ÷ 55		
RH operating humidity (%):	25 ÷ 75		
IP protection rating (IP code):	IP54		
Vandal Resistant rating (IK code):	IK08		
Backlighting colour:	White		

1216

SIMPLEBUS/KIT SYSTEM TERMINAL



Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.

1209

2-WIRE VIDEO KIT POWER SUPPLY UNIT



33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).

MAIN FEATURES - 1209 Supply voltage (VAC): 110÷240 Input connector: Terminal block Applicable to DIN rail: Yes Number of DIN modules: 6 Max. current delivered (A): 1,2



8461V

QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.

ACCESSORIES



4791

Adapter plate for Quadra

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm



4792

RAIN SHIELD FOR QUADRA ENTRANCE PANEL

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W \times H \times D): 99 \times 210 \times 41 mm.



4793MB

BLACK FACEPLATE FOR QUADRA W/BUTTONS

Black faceplate for Quadra entrance panel with mechanical buttons



4793MC

CORTEN FACEPLATE FOR QUADRA W/BUTTONS

Corten color faceplate for Quadra entrance panel with mechanical buttons.



4793MA

ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS

Aluminium colour faceplate for Quadra entrance panel with mechanical buttons

1217

NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates



8461V

QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.



1235A

NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website

6710



BACKPLATE AND DISTRIBUTION TERMINAL FOR MINI MONITOR

Wall-mounting or residential series box backplate for MINI monitor, /BM versions with handset featuring magnetic induction for hearing aid wearers. Also includes riser distribution terminal Art. 1214/2C. Dimensions 145x100x4 mm.

C= 1 2 3 4 5 6 6

6733W

ADDITIONAL BUTTONS KIT FOR MINI MONITOR, WHITE

Accessory for transforming MINI monitors Art 6700W-/BM and 6701W-/BM into versions with 8 buttons. Includes an 8-button faceplate and an electronic module for activating the buttons, which can be installed quickly without opening up the monitor.



6720

Access. cables external passage for MINI HF. S2

Wall support bracket for handsfree Mini monitor allowing thru-routing of external cables.



6732

DESK BASE FOR HANDSFREE MINI MONITOR

Desk base for desktop conversion of Handsfree Mini monitor. Complete with 1x 2 metre cable with RJ45 connector to connect monitor terminals to the coupler or domestic series socket. Dimensions: 140x190x140mm.



1209

2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).



8461V

QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.

ACCESSORIES



1229A

ADDITIONAL RINGTONE ACCESSORY. S2

Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24mm.



1256

ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR

Intelligent Simplebus device for controlling a 12-24 V relay contact. If used in mixed audio/video systems, the actuator relay needs a video filter to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 66X85X35 (4 DIN modules).



1404

DIGITAL SWITCHING DEVICE. 2-WIRE SYSTEM

Audio/video switching module for Simplebus 2 2-wire digital systems. To be used in systems with more than one entrance. Power supply from bus line. Dimensions: 60x85x35 mm (4 DIN modules.



1405

DIGITAL EXCHANGE 2 QUADRA INPUTS. S2

Audio/video switching module for audio/video kit systems. For use in systems with a maximum of 2 entrances with Quadra series external unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN modules.



1409

ACCESSORY FOR REMOTE COLOUR CAMERAS, 2-WIRE SYSTEM

Remote camera module for Simplebus 2 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).