



CA0061

1-BUTTON CIAO ENTRANCE PANEL. 2-WIRE ANALOG.



Ciao series outdoor audio entrance panel for 2-wire analogue systems and designed for 1-call systems for kit art. KCA0061. Front panel in synthetic polymer, resistant to atmospheric agents (IP54 protection rating and paint with anti-UV treatment) and acts of vandalism (IK08 protection rating). Complete with call button art. CA9213. Wall installation support included.



CA0061

1-BUTTON CIAO ENTRANCE PANEL. 2-WIRE ANALOG.

| GENERAL DATA | |
|---------------------------------------|--------------------------|
| Type | Monoblock |
| Height (mm) | 172 |
| Width (mm) | 100 |
| Depth (mm) | 28 |
| Product color | Gray RAL 7042 |
| Product weight (g) | 300 |
| Type of finishing materials | Technopolymer |
| Wall-mounted | Yes |
| AUDIO FEATURES | |
| Microphone | 4mm (Ø), Omnidirectional |
| Loudspeaker | 50mm (Ø), 50 Ohm, 0.25W |
| ELECTRICAL CHARACTERISTICS | |
| Type of power supply | External power supply |
| Supply voltage | 12VAC |
| Maximum absorption (W) | 15 |
| HARDWARE FEATURES | |
| Call type | Push-buttons |
| Type of buttons | Mechanical |
| Number of push-buttons (n°) | 1 |
| Backlight colour | White |
| SETTINGS | |
| Loudspeaker volume | Yes |
| Microphone volume | Yes |
| ENVIRONMENTAL AND COMPLIANCE FEATURES | |
| IP protection rating | IP54 |

**CA0061****1-BUTTON CIAO ENTRANCE PANEL. 2-WIRE ANALOG.****ENVIRONMENTAL AND COMPLIANCE FEATURES**

| | |
|---------------------------------|--|
| Operating temperature (°C) | -25 ÷ 55 |
| Operating humidity (RH max) (%) | 20 ÷ 95 |
| Environmental class | IV |
| CE certifications | RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011) |

MAIN FUNCTIONS

| | |
|-------------------------------------|-----|
| Input for local door release button | Yes |
|-------------------------------------|-----|