

VIDEO DOOR ENTRY SYSTEMS & KITS KIT AUDIO EXTRA





KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



The kit includes: two Mini series door-entry phones art. 2701W, one transformer art. 1200, one Extra series external unit with 2 call buttons art. ET5002. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the relevant accessories supplied with the kit.

AWARDS









KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

KIT PRODUCTS



ET5002 Extra 4+N. series entrance panel kit. 2 buttons

Extra series external unit with 2 call buttons. Stainless steel cover and white nameplate backlighting. Complete with flush-mounted box and wall bracket. Dimensions 95 x 135 x 6.5 mm (flush) - 25 mm (surface). 5-Wire cabling.

GENERAL DATA	
Flush-mounted	Yes
Wall-mounted	Yes
HARDWARE FEATURES	
Clamps	~* ~ 2 3 4 S1 S2
ENVIRONMENTAL AND COMPLIANCE FEATURES	
Operating temperature (°C)	-25 ÷ 55



VIDEO DOOR ENTRY SYSTEMS & KITS

KIT AUDIO EXTRA



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

2701W 1-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Dimensions: $105 \times 191 \times 28$ mm

GENERAL DATA	
Height (mm)	190
Width (mm)	103
Depth (mm)	30
Product color	White
Product weight (g)	260
Wall-mounted	Yes
Desk base-mounted	Yes
COMPATIBLE SYSTEMS	
Traditional system	Yes
AUDIO FEATURES	
Microphone	4mm (Ø), Omnidirectional
Microphone ELECTRICAL CHARACTERISTICS	4mm (Ø), Omnidirectional
	4mm (Ø), Omnidirectional
ELECTRICAL CHARACTERISTICS	
ELECTRICAL CHARACTERISTICS Supply voltage	
ELECTRICAL CHARACTERISTICS Supply voltage HARDWARE FEATURES	15÷16VDC
ELECTRICAL CHARACTERISTICS Supply voltage HARDWARE FEATURES Clamps	15÷16VDC S 2 3 4 P1 1
ELECTRICAL CHARACTERISTICS Supply voltage HARDWARE FEATURES Clamps Total buttons (n°)	15÷16VDC S 2 3 4 P1 1
ELECTRICAL CHARACTERISTICS Supply voltage HARDWARE FEATURES Clamps Total buttons (n°) ENVIRONMENTAL AND COMPLIAND	15÷16VDC S 2 3 4 P1 1 CE FEATURES

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.



VIDEO DOOR ENTRY SYSTEMS & KITS

KIT AUDIO EXTRA





KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

Absorption during call (mA)	0.42
Absorption during communication (mA)	0.35
Key button function	Yes
Loudspeaker volume control	Yes
Microphone volume control	Yes
Ringtone volume control	Yes
Audio system	Yes
Electronic bell	Yes



VIDEO DOOR ENTRY SYSTEMS & KITS

KIT AUDIO EXTRA



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



1200 TRANSFORMER 10VA 0-230V/0-12V

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use.Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES	
Supply voltage	230
Input connector	Terminal block
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9

GENERAL DATA	
Height (mm)	95
Width (mm)	53
Depth (mm)	65
Type of finishing materials	Plastic
Operating temperature (°C)	-5 ÷ 40

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Semplified system	Yes

ELECTRICAL SPECIFICATIONS	
Maximum power delivered (W)	15

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.







KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

ACCESSORIES

ET9150	Flush-mounted box for Extra entrance panel kit Flush-mounted box for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 134.5 x 93.5 x 25 mm
ET9160	Wall bracket for Extra entrance panel kit Wall housing for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 94 x 134 x 19 mm
1229	EXTENSION SOUNDER Additional bell for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surfacemounted or on civil series 503 box. Dimensions: 110X75X29 mm.

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.