



**UT2010VC**

**ULTRA SIMPLEBUS2 AUDIO MODULE FOR REMOTE CAMERA**



Audio module with facility for connection of an analogue remote camera with PAL standard for Ultra entrance panel, Simplebus 2 system. To be used in systems with power supply art. 1210/1210A. Easy to install and configure, thanks to the smart programming of call buttons. Twilight sensor for automatic nameplate backlight switch-off during daytime hours. Omnidirectional digital microphone and dual loudspeaker for high-fidelity audio. Programmable audiovisual functions for users with disabilities. Designed for 2 call buttons. To be finished with cap, single button or double button in professional-grade plastic given an anti-yellowing and anti-dulling treatment or in aluminium. Adjustment and programming can be carried out without removing the module. Dimensions: 1 Ultra module. ULTRA, the new and most technologically advanced entrance panel offering maximum ease of installation. Available in flush-mounting (10 mm protrusion from the wall) or surface-mounting (just 35 mm protrusion from the wall) versions. Dimensions: 100x90x35mm

**AWARDS**



## UT2010VC

### ULTRA SIMPLEBUS2 AUDIO MODULE FOR REMOTE CAMERA

#### GENERAL DATA

Type	Modular
Height (mm)	90
Width (mm)	100
Depth (mm)	35
Product color	Aluminium, Black RAL9005, Transparent
Product weight (g)	265
Type of finishing materials	Polycarbonate, Aluminium alloy
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

#### COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
---	-----

#### AUDIO FEATURES

Microphone	MEMS audio digital sensor, omnidirectional
Loudspeaker	28mm (Ø), 8 Ohm, 1W (2)

#### ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Absorption in stand-by (W)	1.5
Maximum absorption (W)	4

#### HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	2
Backlight colour	White, Off
Clamps	L L V+ V- COM NC NO SE+ SE-/GND RTE TX- TX+ RX- RX+



## UT2010VC

# ULTRA SIMPLEBUS2 AUDIO MODULE FOR REMOTE CAMERA

## HARDWARE FEATURES

Number of inputs (n°)	1
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 4A@12÷24 VAC/VDC, 10A peak)
Communication ports	Micro-USB
Twilight sensor	Yes

## SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes
Backlight brightness	Yes

## PROGRAMMING MODE

Manual programming (via Dip Switch)	Yes
ViP Manager software	Yes

## ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

## MAIN FUNCTIONS

Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes
Visual indications of system status	Yes



**UT2010VC**

**ULTRA SIMPLEBUS2 AUDIO MODULE FOR REMOTE CAMERA**

**MAIN FUNCTIONS**

Acoustic signals of system status	Yes
Speech synthesis of system status	Yes