





VISTOCAM360

3D VIEW INDOOR SMART CAMERA. VISTO SYSTEM



The Smart 3D indoor camera is a revolutionary camera that allows you to view the image with a 4MP quality and rotate it in any direction, to communicate with anyone near it and to record on the micro-SD card, avoiding the loss of important events even in the absence of connection, for a 360° protection.





VISTOCAM360

3D VIEW INDOOR SMART CAMERA. VISTO SYSTEM

| | MAIN FEATURES |
|----------------------------------|---------------------------|
| Camera sensor | 1/3'' CMOS |
| Lens optical dimensions (mm) | 1.2 |
| Diagonal FoV (°) | 360 |
| Sensitivity (lux) | 0 (led IR ON) |
| IR filter | Mechanical |
| Video resolution (H x V - pixel) | 1920x1080 (Full-HD 1080p) |

| SOFTWARE/FIRMWARE SPECIFICATIONS | |
|----------------------------------|----------------------------------|
| Video compression | H.264, H.265 |
| Frame rate | 25fps |
| Remote control by mobile | App Comelit Visto (Android, iOS) |
| | |

| FUNCTIONS | |
|--------------------------|---|
| Main functions | Push notification, Wi-Fi, Audio two way, full-duplex, echo canceler, noise canceler, Micro-SD (class 10, max 32GB), local and cloud video recording |
| Motion detection (zones) | 1 |

| HARDWARE SPECIFICA | TIONS |
|--------------------|-------|

| No. IR LEDs / Max. distance | 3 led / 5m |
|-------------------------------------|------------|
| Support SD card (card not included) | Yes |

| | GENERAL DATA |
|-----------------------------|----------------------------------|
| Max absorption (W) | 5 |
| Type of power supply | Micro-USB, External power supply |
| Diameter (mm) | 56 |
| Height (mm) | 115 |
| Product weight (g) | 170 |
| Type of finishing materials | Polycarbonate |
| Product color | White RAL9003 |
| Operating temperature (°C) | 5 ÷ 40 |

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.





VISTOCAM360

3D VIEW INDOOR SMART CAMERA. VISTO SYSTEM

| | GENERAL DATA |
|---------------------------------|--------------|
| Operating humidity (RH max) (%) | 25 ÷ 75 |
| Supplied accessories | Power supply |