



VISTOCAM/E

OUTDOOR CAMERA FOR VISTO SYSTEM



The Visto outdoor camera allows you to have alternative views of the exterior of the house, the workplace and yard. It allows a high level of security and monitoring of areas such as walkways, garages, entrances and alleys.

AWARDS

DESIGN
MILANO



VISTOCAM/E

OUTDOOR CAMERA FOR VISTO SYSTEM

MAIN FEATURES

Camera sensor	1/4" CMOS
Lens optical dimensions (mm)	2.5
Horizontal FoV (°)	91.6
Vertical FoV (°)	50
Diagonal FoV (°)	108
Electronic shutter (s)	1/25÷100000
Sensitivity (lux)	0 (led IR ON)
IR filter	Mechanical
Video resolution (H x V - pixel)	1280x720 (HD 720p), 320x240

SOFTWARE/FIRMWARE SPECIFICATIONS

Video compression	H.264
Frame rate	25fps
Protocols supported	802.11b/g/n (Wi-Fi, 2.4GHz), DDNS, DHCP, HTTP, NTP, SMTP, TCP/IP, P2P
Network security	WEP, WPA, WPA2
Remote control by mobile	App Comelit Visto (Android, iOS)

FUNCTIONS

Main functions	Push notification, Wi-Fi, Local and cloud video recording
----------------	---

HARDWARE SPECIFICATIONS

No. IR LEDs / Max. distance	24 led / 12m
IP protection rating	IP54
LAN output type	Ethernet 10/100 Mbit/s (RJ45)

GENERAL DATA

Max absorption (W)	12
Diameter (mm)	70
Depth (mm)	200

**VISTOCAM/E****OUTDOOR CAMERA FOR VISTO SYSTEM****GENERAL DATA**

Product weight (g)	310
Type of finishing materials	Die-cast aluminum
Housing type	Bullet
Product color	Dark graphite RAL9011
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 75
Supplied accessories	Power supply