

DHI-VTO2010D Analog Villa Door Station



Technical Specification

DHI-VTO2010D

DIII-0102010D	
Button Type	Mechanical keyboard keys
Camera	1/2.7" 2MP CMOS
Field of View	H:70°, V:38°, D:82°
Focal Length	3.3 mm
IR	Support
Audio In	1 channel to the microphone, pickup distance 0.5m
Audio Out	1 channel to the speaker
Indicator Light	1 indicator light; Green: Power on
Communication Method	Analog
Unlock Mode	Local unlock
Exit Button	1
Appearance Color	Black
Installation Mode	Surface
Certification	CE FCC
Dimensions	134.9 mm × 47.2 mm × 33.8 mm (5.31" × 1.86" × 1.33")
Protection Grade	IK07, IP65(Apply silica gel to gaps between the device and the wall.Liquid sodium silicate is recommended. For details, see the quick start guide.)
Operating Temperature	-30° C to +50° C (-22°F to +122°F)
Operating Humidity	10%RH -95%RH
Power Consumption	≤1W (standby mode) ≤3W (operating)
Net Weight	0.19 kg (0.42 lb)

• IR night vision

- Color video intercom
- Echo cancelation
- Mechanical button
- 4-Wire connection
- Plug & Play
- Metal material
- IK07&IP65(Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)

Dimensions (mm[inch])







Application



Rev 001.001 © 2020 Dahua. All rights reserved. Design and specifications are subject to change without notice Pictures in the document are for reference only, and the actual product shall prevail.